

# Canadawide

SCIENTIFIC

www.canadawide.ca 1-800-267-2362 100% Canadian Owned ISO 9001:2008 Registered

Research




Analysis



Solution



Laboratory



Science



**Equipment  
Winter  
2011**

Prices valid until  
January 31, 2012

## NEW Revco UxF Series ULT Freezer

- Outstanding temp uniformity. Door opening recovery in 28 mins.
- Touch-screen control panel shows alarms, door openings, temp, backup system and environmental conditions.
- 5 polystyrene insulated inner doors.
- Store up to 15 years of data on the on-board computer.
- 24.1cu.ft. Holds 500 x 2" cryoboxes.



Cat. #D746-694-88



## NEW Revco CxF Series Chest Freezer

- Temp range: -10 to -40°C. 12.7 cu. ft.
- LED display.
- Inner sub-lids protect samples from ambient exposure.
- Steel exterior with powder coated finish. Stainless steel interior.
- Warranty: 5 years (parts and labour).



Cat. #D746-688-18



## NEW GP Series Chromatography Refrigerator

- Temp range: 1 to 12°C (factory setpoint 4°C).
- Digital temp controller and display.
- High/low visual and audio alarms.
- Control panel with key lock.
- Interior duplex outlet.
- Capacity: 45cu.ft.



Cat. #D746-634-26

**PROMO** Get 10 FREE inventory storage racks with purchase.

## NEW Stirling Ultracold Shuttle™ Portable -86°C Freezer

- Ideal for field use, transportation, bench top storage; dry ice alternative.
- 25 L capacity, lightweight and compact.
- HFC-free refrigerants.
- Supplied with AC adapter and 3m cord for vehicle power outlet.



Cat. #	Description	Temp. Range, °C
D746-638-30	Digital, set temp. in 1°C increments	-86 to -20

## NEW Portable +4°C Refrigeration Unit

- Ideal for blood/vaccine transport or storage.
- 25L capacity; lightweight at just 32lbs.
- Maintains +4 to 8°C, ±1°C; with internal heater.
- HFC-free refrigerants.
- Includes 12V DC vehicle power cord and AC adapter.



Cat. #D746-637-52

## NEW Heratherm® General Protocol Oven

- Temp range: 50 to 250°C ±4°C at 150°C.
- Gravity convection.
- Ideal for gentle drying and heating with low air turbulences.
- Easy calibration routine.
- Large vacuum-fluorescent display.
- 120V.



Cat. #D627-315-02

## NEW Heratherm® General Protocol Incubators



- Temp range: ambient + 5 to 75°C. Uniformity: ±0.6°C.
- Gravity convection.
- Over-temp alarm.
- Corrosion-resistant stainless steel interior.
- Stackable without tools or stacking kits.

Cat. #	Volume
D579-658-02	2.6cu. ft; 75L
D579-658-04	4.0cu. ft; 117L
D579-658-06	6.85cu. ft; 194L

## NEW Stirling Ultracold Undercounter ULT Freezer

- Uses up to 50% less energy than conventional freezers.
- Volume: 3.7cu.ft (105L). Undercounter, benchtop or stacked configuration.
- Temp range: -20 to -86°C. Uniformity: ±1.0°C.
- Humm™ free-piston engine requires no maintenance.
- Unlike conventional cooling systems that turn on/off, Humm™ system operates continuously to minimize uniformity deviations.



Cat. #D746-632-11

## Locator 6 Cryogenic Storage Vessel

- Compact, liquid nitrogen, cryo-biological storage vessel.
- Super-insulated wall and narrow mouth minimizes liquid nitrogen "boil off".
- Lockable vessel lid prevents unauthorized entry.
- Complete with stainless steel storage racks.
- Volume: 184L.




Cat. #D338-100-06



**PROMO** Get a FREE wheeled cart with purchase.

## CUBIS Balances

- 1-digit to 7-digit resolution – toploading to ultra-micro balances.
- Modular design so you only invest in what you require, with flexibility to grow as required.
- Choose from 3 displays, 24 weighing modules and 6 draft shields.
- Automatic doors on micro- and ultra-balance draft shields. Optional built-in ionizer eliminates electrostatic charges inside the chamber.
- Assisted levelling on all models. Automatic levelling also available for toploading and analytical balances.
- Warranty: 3 years.



## Sartorius CP Series Analytical Balance

- Innovative all-glass draft shield, with smooth-action doors.
- % weighing, animal weighing, net-total and below balance weighing.
- Stainless steel triangular pan (3.1" dia.) allows 27% more surface space for samples.
- Readability: 0.01/0.1mg; Capacity: 100/200g.
- Warranty: 3 years.



Cat. #D111-079-20

## Sartorius M-Prove Toploading Balances

- Applications include counting, percent weighing, totalling, display hold, specific gravity and mass unit conversion.
- Stackable with protective flip-down cover.
- Integrated external calibration weights and AC adapter included.



Cat. #	Capacity	Readability	Pan Size
D111-898-06	210g	0.01g	3.8" dia.
D111-898-10	610g	0.01g	5.5 x 5.0"



**PROMO** Get a FREE accessory with purchase.

## Sartorius Moisture Analyzer

- Results in % moisture, % total solids, and weight.
- Max capacity: 35.0g. Temp range: 40 to 160°C.
- Results in 5 to 15 minutes.
- Infrared heating element.
- No glass components – in compliance with HACCP regulations.



Cat. #D112-395-02

## Sartorius Midrics Balance

- Can handle high impact, vibration, dust, dirt, water, aggressive cleaning agents or overloading.
- Capacity: 6 kg/0.0005 kg.
- Completely washdown.
- Four adjustable levelling feet, built-in level indicator and overload stop.



Cat. #D112-110-04

Indicator holder (bench, wall or column) must be ordered separately when ordering a scale.

**PROMO** Get a FREE accessory with purchase.

## NEW Ohaus® Navigator™ Scale

- Applications: counting, % weighing, checkweighing, display hold and accumulation/totalization.
- Two touchless sensors.
- Set up to 36 combinations of functions without touching keys.
- Measures lb, oz, lb:oz, kg, g, troy ounce, grain, Newton, carat, pennyweight, Tael, Tical and Tola.
- Overload protection up to 4 times its capacity.
- 6400g/0.5g



Cat. #D112-095-06

## NEW Thermo Orion® Star A329 Portable pH/ISE/Cond/RDO/DO Meter

- Display shows up to 3 parameters with temp, plus electrode status, time, date, sample ID, user ID and calibration points.
- Up to 5-point pH calibration with auto recognition of buffers.
- Holds up to 5000 data points with time and date stamp.



Cat. #D639-890-02

Includes 4 x AA batteries.



## NEW Thermo Orion® Star A211 Benchtop pH Meter

- Range: (pH) -2.000 to 20.000; (mV) ±2000.0; (temp) -5.0 to 105.0°C.
- Display shows pH/mV/RmV/Temp with electrode status, time, date, sample ID, user ID and calibration points.
- Up to 5 point pH calibration with auto recognition for buffers.
- Holds up to 2000 data points with time and date stamp.



Cat. #D640-320-02

Includes AC adapter, electrode arm and probe holder.



## Thermo Orion® Star A323 RDO/DO Portable Meter

- Backlit graphic LCD display shows DO in % saturation or concentration with temp, electrode status, time, date, sample ID, user ID and calibration points.
- Meter automatically recognizes Orion polarographic and RDO optical/luminescence-based probes.
- Accurate results are easy with ATC, manual salinity and auto/manual barometric pressure compensation.
- Holds up to 5000 data points with time and date.



Cat. #D628-275-02

Comes with 4 x AA batteries.



3 year meter replacement warranty.

## Misonix AURA 42" Ductless Fume Hood

- Filtrak® filter locking system ensures an airtight seal to prevent fumes from bypassing the filter.
- HEPA or carbon filters sold separately by application. Two pre-filters included.
- Removable fibreglass spill tray.
- Powder coated aluminum head and chassis.

Cat. #D504-200-04



## Misonix PCR Prep Station

- Laminar flow enclosure reduces risk of sample contamination while performing PCR experiments.
- 99.997% efficient HEPA filter (included with prefilter).
- UV light to prevent cross contamination. Stainless steel tray.

Cat. #D504-300-11



## Misonix Ductless Economy Workstation

- Compact, lightweight workstation captures fumes and particulate matter.
- Adjustable air speed from 0 to 120 fpm.
- Fits over a sink.
- Made of epoxy-coated aluminum. Base section is clear 1/4" acrylic with a hinged front sash.

Cat. #D504-010-11

Includes an electrostatic pre-filter.



## Captair® Chemical Filtering Cabinet

- Ideal for storing compatible and/or incompatible, noxious or odorous chemicals.
- Store up to 100 one-litre bottles.
- Supplied with eight adjustable shelves and spill tray.
- No ducting required. Can be installed anywhere in the lab.

Cat. #D765-960-04



## Captair® Flowcap 700 Laminar Flow Cabinet

- Ideal for operations in a sterile environment or where protection of the sample is essential.
- HEPA filter is 99.999% effective at removing 0.3µm particles.
- Air flow meter system constantly monitors air face velocity and indicates blockages of the HEPA filter.

Cat. #D504-000-11



## Plas-Labs Basic Glove Box

- Clear, one-piece acrylic top is sealed airtight to the thermoset base.
- Supplied ambidextrous Hypalon gloves have superior chemical and UV resistance.
- Glove ports measure 8.75" in diameter.
- Includes four ground key cock valves for purging, an adjustable vacuum gauge and a white leveling tray for transferring liquids into the work chamber.


Cat. #D552-750-02



## Motic K-Series Stereo Microscope

- Common Main Objective (CMO) Infinity Optical System.
- 45° binocular head. Widefield eyepieces 10X/FN. 23.
- Standard 1X Achromatic Objective with 6X, 12X, 25X and 50X magnification.
- Large working surface incident illumination stand.
- No built-in illumination.

Cat. #D598-725-02




## Motic BA310 Compound Microscope

- Siedentopf head type 30° inclined, 360° rotatable. Binocular.
- Diopter adjustment on both eyepieces. Rubber eyecups.
- Reversed quintuple nosepiece with CCIS EF-N Plan Achromat objectives 4X, 10X, 40X S, 100X S-oil.
- Built-in halogen illumination 6V/30W (Koehler Type).
- 100-240V.

Cat. #D598-450-06


Supplied with a 45mm blue filter, vinyl dust cover, Allen hexagonal key and power cord.



## NEW Mettler-Toledo Quick-Brix™ Meter

- Compact and portable.
- Splash-proof design, can be rinsed off for cleaning.
- Calibrateable with a single key using just water.
- Measures Brix from 0 to 90%. Accuracy: ±0.1%.
- Temp range: 10 to 75°C.

Cat. #D746-190-02



## Sartorius Arium® PRO Water System

- ASTM Type 1 water purification system for the high end user.
- Product water quality:  
Resistivity: 18.2 MΩ x cm. Particles: < 1/ml (at 0.2 µm). Bacteria: < 1 CFU/1000ml.
- Volume and time controlled dispensing.
- Adjustable flow rate up to 120L/hr.



Cat. #D966-153-02

Visit [www.canadawide.ca](http://www.canadawide.ca) for all Arium® PRO water systems.



**PROMO** Get a FREE dispenser gun and cartridge with purchase.

## Heraeus® Megafuge 16R Bundle

- Max. capacity: 4 x 400ml. Max. RCF: 25,701 x g.
- Temp range: -10 to 40°C with pre-cooling.
- Large, backlit display. Easily adjust speed, time and temp, even during a run.
- Comes with Megafuge 16R centrifuge, TX-200 rotor, four TX-200 buckets, four ClickSeal™ biocontainment lids, four 7x10/15ml and four 8x5/7ml blood collection adapters.



Cat. #D250-854-11

## NEW Barnstead RO Water Systems

- Includes all required components for setup.
- Provides purified water for general lab use or feeding source to an ultrapure water system.
- Contaminant rejection: (organic) 99%; (particulate) 90 to 95%; (microbiological) 99%; (minimum ionic) 90 to 95% monovalent, 95 to 99% polyvalent.



Cat. #	Flowrate
D966-175-02	6 L/hr
D966-175-04	12 L/hr
D966-175-06	24 L/hr



**PROMO** Buy a 12 or 24 L/hr RO water system and get a FREE 30L or 60L reservoir.

## Thermo Scientific® Medilite Centrifuge

- Ideal for routine, low-volume, blood and urine separations.
- Holds up to six 15ml or twelve 10ml tubes.
- Spins at 3100rpm (1228 x g).
- Includes a 45° fixed angle rotor and standard tube shields.



Cat. #D250-531-10

## NEW HotPack Undercounter Glassware Washers

- 304 stainless steel chamber and exterior.
- Temp up to 70°C for optimal cleaning.
- Volume: 6.0ft<sup>3</sup>; 170L.
- Six selectable washing cycles. Two loading levels.
- Final DI rinses for all cycles.
- 115V.



Cat. #	Drying
D979-000-02	Standard
D979-000-04	Heated

## Heraeus® Pico/Fresco Microcentrifuges

- Includes 24x1.5/2.0ml rotor with ClickSeal™ bio-containment lid.
- Supports micro-volume protocols such as nucleic acid or protein lysate preparation and PCR reaction set-up.
- Max. force: 21,000 x g. Max. speed: 14,800rpm.
- Temp range: -9°C to 40°C for #250-675-08.



Cat. #	Description
D250-675-06	Pico, ventilated
D250-675-08	Fresco, refrigerated



**PROMO** Get a FREE additional 2-year extended warranty with purchase.

## NEW Celltreat™ Centrifugation Flip-Top Tubes

- Made of high-clarity polypropylene.
- Bold, easy-to-read graduations.
- Sterile, gamma irradiated, RNase-free, DNase-free, DNA-free and non-pyrogenic.
- One-hand removal of caps helps prevent contamination.
- Temp range: -80 to 120°C. Case of 500.




Cat. #	Volume	Packaging
D917-500-20	15ml	Rack
D917-500-22	15ml	Bag
D917-500-24	50ml	Rack
D917-500-26	50ml	Bag



## Celltreat™ Serological Pipets

- Printed with bold clear bi-directional graduations (±2%).
- Colour coded packs and individually wrapped in sterile paper/plastic packaging.
- Gamma irradiation sterilized.



Cat. #	Capacity/Graduations	Case
D917-350-12	1 ml/0.01 ml	800
D917-350-13	2 ml/0.02 ml	600
D917-350-14	5 ml/0.1 ml	200
D917-350-15	10 ml/0.1 ml	200
D917-350-16	25 ml/0.2 ml	200
D917-350-17	50 ml/0.5 ml	90



**PROMO** Buy any 3 cases of Celltreat product, get one case FREE.

## NEW eLine® e5 Micro Electronic Pipettors

- With super pipetting function.
- Dispense the smallest volume easily and precisely.
- Volume range: 0.1 to 5µl. Increments: 0.05µl.
- No need to touch the receiving vessel wall or dispense under the liquid surface.



Cat. #	Description
D707-227-02	Without adapter
D707-227-04	With adapter

NOTE: Uses the Biohit 10µl tips.



**PROMO** Get a FREE charging stand with purchase.

## NEW Precisa PrepASH® Automatic Ashing & Drying System

- Up to 29 samples in one cycle without a desiccator.
- Temp range: 50 to 1000°C.
- 3-step process. Error-free results.
- End-point recognition replaces drying oven and muffle furnace.
- Built-in analytical balance.
- Capacity: 120g. Readability: 0.0001g.
- Max. analysis time: 36 hours.
- 5.7" VGA colour touch-screen.
- Power: 230V.



Cat. #D355-000-02

Call for a quotation or demo.

## NEW Dynamica Halo DB-20 UV/Vis Spectrophotometer

- Ensures concurrent measurement of the sample and reference for improved stability, accuracy and reproducibility.
- Spectral bandpass: 1.5nm.
- Scan speeds from 10 to 3600nm/min.
- Dual halogen tungsten and deuterium lamp system. Lamp switching is automatic and selectable from 325nm to 370nm. Silicon photodiode detector.
- Wavelength Range: 190 to 1100nm. Accuracy: ±0.3nm.



Cat. #D793-999-11

## ACP Chemicals Disposable Dilution Bottles

- Come fully prepared for immediate use. Pre-filled aseptically with sterile dilution water.
- Contains purified water, monobasic potassium phosphate, and sodium hydroxide for pH adjustment. pH range of 7.2 ± 0.2.
- Case of 72.



**\$79**

Cat. #	For	Diluent fill
D187-300-02	Food/pharma.	99 ± 2
D187-300-04	Food/pharma.	90 ± 2
D187-300-20	Wastewater	99 ± 2
D187-300-22	Wastewater	90 ± 2

## NEW Astoria Pacific Discrete System

- Discrete analyzer for water, soil and wine analysis.
- Very low reagent consumption.
- Four active colorimetric detectors, 60 and 96-place sample racks, 27-place reagent tray.
- Performs many common tests like ammonia, cyanide, nitrate, nitrite, phenol, ortho-phosphate, total Kjeldahl nitrogen and total phosphorus.



Cat. #D101-550-11

Call for a quotation or demo.

## NEW Dynamica LEDetect Microplate Reader

- Computer controlled microplate reader for 96-well plates.
- Single and dual wavelength measurements.
- Reading speed: 5 seconds (single wavelength); 10 seconds (dual wavelengths).
- No lamp replacements.
- Wavelength range: 340-750nm (special wavelengths up to 900nm).



Cat. #D729-500-11

Supplied with PC software Capture96 and MikroWin2000 (demo version), power adapter, USB cable, 4 standard filters and user manual.

## Kord-Valmark Disposable Petri Dishes

- Clear top and bottom viewing surfaces.
- Moulded from medical grade virgin polystyrene.
- Ventilation ribs reduce condensation and allow free air circulation.
- Slippable dishes are ideal for use in automated equipment.
- Traceable to standards provided by NIST.



Cat. #	Type	Size	Case
D372-600-30	Stackable	100x15mm	500
D372-600-10	Slippable	100x15mm	500
D372-600-24	No rim	150x15mm	100

## NEW Thermo Scientific® Savant SpeedVac Concentrator Kit

- Ensures consistent drying times and reproducible results.
- Equipped with a vacuum pump that ensures a gentle transition from atmosphere to vacuum setting, eliminating sample disturbance from bumping.
- Three temp settings: ambient, 43°C or 65°C.
- Concentrator Volume: 0.4 to 100 ml.
- Concentrator Capacity: 4 to 120 tubes.



Cat. #D315-000-02

Comes with a 64-place microcentrifuge tube rotor and two glass condensation flasks.

## NEW Atago ABBE NAR-4T Refractometer

- Refractometer for high refractive index samples. Measures refractive index only.
- Range: 1.4700 to 1.8700nD. Accuracy: ±0.0002.
- Temp range: 5 to 50°C.
- LED light source.



Cat. #D746-268-11

Includes a test piece, D line (589nm) light source and monobromonaphthalene to calibrate (for measuring solid samples).

## NEW Berkshire CapSure™ Cleanroom Wipers

- Sterile, sealed-edge cleanroom 100% polyester knit wiper.
- Designed for ISO Class 3 and higher sterile environments and cleaning sterile surfaces.
- Surface treated wiper captures 42 times more particles and retains 93% of particles captured.
- Chemically compatible with common cleaning solutions.
- 12 x 12". Case of 2500.



Cat. #D310-250-11

## NEW Heracell 150i CO<sub>2</sub> Incubator

- Temp range: ambient + 3 to 55°C ±0.3°C at 37°C.
- CO<sub>2</sub> range: 0 to 20%. TC CO<sub>2</sub> sensor.
- Humidity: ambient to 95% at 37°C.
- iCAN™ full colour touch-screen display.
- Logs user interaction activities, such as door openings and parameter changes.
- 5.3 cu. ft. (150 L).



Cat. #D579-735-02

## Forma Stackable Incubated Shakers

- Designed for high volume scale-up culture, research at different temps and speeds, and high volume research in labs with limited space.
- Speed range: 25 to 400 rpm. Orbit = 1".
- Max. capacity per unit: 70 lbs.
- Platforms and clamps sold separately.



Cat. #	Description	Temp Range
D779-105-02	Incubated	Ambient + 10 to 60°C
D779-105-06	Incubated/Refrigerated	Ambient - 20 to 60°C

## NEW Max Q™ 6000 Heated/Refrigerated Shakers

- 7.2 cu.ft. Stackable.
- Speed: 15 to 500rpm (unstacked); 15 to 300rpm (stacked).
- Continuous/timed operation.
- Electrical outlet inside chamber.
- Visual/audible alarms, unbalanced load sensor, soft-start feature, and safety interlock.



Cat. #	Description	Temp range
D778-998-02	Incubated	Ambient +10 to 80°C
D778-998-06	Incubated/Refrigerated	Ambient -15 to 80°C

NOTE: Either the universal or dedicated platform is required for use (sold separately). Two adjustable shelves included.

## Max Q™ Shaking Waterbath

- Handles heavy workloads (max. 16kg) and provides smooth agitation.
- Total capacity: 18L. Twin baffles minimize splashing and turbulence.
- Temp range: ambient + 5°C to 65°C.
- Orbit: 0.5". Shaking: 15 to 500rpm.
- Digital display shows speed and operating time.
- Shaker platform and clamps sold separately.



Cat. #D124-549-04

**PROMO** Get a **FREE** universal platform, and 5 clamps or 1 unwire test tube rack with purchase.

## Cimarec® Hot Plate-Stirrer

- High-impact ceramic top heats to 540°C in 8 minutes.
- Adjustable speed range from 100 to 1200rpm.
- Includes a TFE-coated stir bar.
- 7 x 7" plate.



Cat. #D565-388-04

## Grant SBB Aqua Plus Waterbath

- 5L capacity. Boiling, analog, unstirred water bath.
- Continuous 100°C operation.
- Constant level device maintains liquid level.
- Supplied with perforated tray and non-drip polycarbonate lid.



Cat. #D124-455-02

## NEW Thermo Scientific® Digital Peristaltic Pumps

- Speed: 4 to 400rpm.
- Self priming, able to operate dry and contains no valves or seals, eliminating replacement needs.
- Contamination free pumping - the fluid contacts only the tubing material.
- Reversible pump direction permits purging of tubing.
- Remote control capability - ideal for automated process applications.
- Stackable.



Cat. #	Flowrate
D739-200-02	0.5 to 3000ml/min
D739-200-04	14 to 4000ml/min

## NEW Fendall 2000 Primary Emergency Eyewash Device

- Self-contained, no plumbing required.
- 24-month cartridge life.
- Built-in alarm sounds when the unit has been activated, and again when the required 15-minute flush has been completed.
- Arm/headrest provides user comfort.
- Meets ANSI Z358.1-2009 requirements for primary eyewash stations.



Cat. #	Description
D767-395-11	Fendall 2000 Eyewash
D767-395-30	Sterile Saline Cartridge

Supplied with emergency eyewash station sign, mounting bracket, installation DVD and tamper-seal. Sterile saline solution cartridge NOT included.

## NEW Hanna Karl Fischer Titrator

- Ultra-high precision system with magnetic stirring, endpoint determination, dynamic dosing and background drift correction algorithms.
- Supports up to 100 titration methods.
- Clip-Lock™ system enables exchange of burettes in seconds and prevents cross contamination.
- Range: 100ppm to 100% water content.



Cat. #D919-983-50

Supplied with dual platinum pin electrode, dosing pump, 5ml burette assembly, air pump assembly, beaker and bottle top assemblies and fittings, 4 desiccant cartridges, stir bar, waste bottle, calibration key, USB cable, power cable, PC application, USB flash drive, quality certificate and ISO 8655 burette compliance report.

## NEW Berkshire EasyClean® 360 Isolator Cleaning Tool

- Will not scratch or damage surfaces.
- Durable, stainless steel mop head swivels 360° for easy maneuverability.
- 4 x 7" triangular head shape improves access in tight corners.
- Mop head and handles can be sterilized by autoclave or gamma irradiation.
- Covers made from Super Polx® 1200 continuous filament polyester wiping material.



Cat. #	Description	Cs. Qty
D310-800-11	Cleaning Tool	ea
D310-800-30	Non-sterile Elastic Covers	150
D310-800-32	Sterile Elastic Covers	200
D310-800-34	Non-woven Covers	200

## Ronco Touch Pink Nitrile Gloves

- Latex-free. Powder-free.
- Superior grip and elasticity. Excellent strength.
- Reduced hand fatigue.
- Resists a wide variety of chemicals.
- Beaded cuffs. Length: 9.5".
- Case of 1000.



**\$99**

Cat. #	Size
D548-482-02	X-Small
D548-482-04	Small
D548-482-06	Medium

## Biohit eLine® Electronic Pipettors

- Unique electronic one-touch tip ejection. Ergonomic.
- Up to 11 pipetting modes. 9 aspirating/dispensing speeds.
- Electronic start button for all pipetting operations.
- Autoclavable lower parts.

**\$699**

Cat. #	Volume Range	Increments
D707-230-12	0.2-10 µl	0.05 µl
D707-230-14	5-120 µl	0.5 µl
D707-230-16	10-300 µl	1 µl
D707-230-18	50-1000 µl	5 µl
D707-230-20	100-5000 µl	10 µl

Also available in 8- and 12-channel.



**PROMO** Get a **FREE** charging stand with purchase.

## NEW Ronco Black Powder-Free Nitrile Gloves

- Ambidextrous. Chlorinated.
- Excellent dexterity and tactile sensitivity.
- Tear and puncture resistant.
- Beaded cuffs. Thickness: 4 mil. Length: 9.5".
- CFIA Accepted.



**\$110**

Cat. #	Size	Case Qty.
D548-450-02	Small	1000
D548-450-04	Medium	1000
D548-450-06	Large	1000
D548-450-08	X-Large	1000
D548-450-10	XX-Large	900

## NEW NCS Specimen Containers

- Streamlined straight sided vials are stable and stackable.
- Constructed of clear polypropylene.
- Packaged 100/bag. Case of 400.
- Volume: 90 ml. Labelled.



Cat. #	Type	Cap Colour
D324-765-05	Sterile	Orange
D324-765-06	Non-sterile	Yellow

## Kimberly-Clark Purple Nitrile Gloves

- Latex-free. Powder-free.
- Superb barrier protection against infectious agents and most chemicals.
- Textured fingertips.
- Thickness: 5.9mil (finger), 4.7mil (palm). Length: 9.5".



**\$157**

Cat. #	Size	Case Qty.
D548-350-02	X-Small	1000
D548-350-04	Small	1000
D548-350-06	Medium	1000
D548-350-08	Large	1000
D548-350-10	X-Large	900

**PROMO** Buy 4 cases, get 1 case **FREE** on select Kimberly-Clark gloves.

**ASK ABOUT NEXT DAY DELIVERY**

Prices valid until January 31, 2012. While quantities last. Prices subject to change without notice. Product specifications are subject to change without notice. Prices not valid with any other promotions or discounts, some promotions are direct with manufacturer.

**Canadawide**  
SCIENTIFIC

2300 Walkley Road  
Ottawa, ON K1G 6B1

